

iSMA-D-PA10C-B1

iSMA-D-PA10C-B1 is 10" Industrial PC Panel with Android 7.1 operating system. It has been designed to simplify the use of Master Application Controller: iSMA-B-MAC36NL. You can connect it to iSMA-B-MAC36NL, JACE or other supervisor powered by Niagara to display graphics by web page from Niagara system. As a Panel PC with Android it can be also used as User Interface. You can install a dedicated application that will allow a communication with other devices in BMS system for example our Android application designed for connectivity with Niagara station. The Aspect Ratio 16:9 with resolution 1366x768 allows for displaying graphics clearly. The panel can be built into the wall, it is compatible with VESA. The panel has an extensive menu in 7 languages, in which we can customize the displayed image.

Key Features

- Android 7.1 operating system
- 10" display with capacitive touch screen
- Aspect Ratio 16:9
- Resolution 1366x768
- Response time 5 ms
- IP65 for front Panel
- Aluminum alloy enclosure
- VESA compatible
- Available with EU, UK and US power supply.



iSMA-D-PA10C-B1

Specification

Display

- Size 10,1"
- Aspect Ratio 16:9
- Resolution 1366x768
- Contrast 800:1
- Luminance 300 nit, up to 800 nit
- Response time 5 ms
- Active Area (mm) 222.7x125.2
- Display colors 16,7 M (8-bit)
- View angle 75/75/75/75
- 10-point capacitive touch screen

Interface

- IP
- TF/SD Card
- 2XRS232
- I/O Audio
- USB 3.0 and USB 3.0/OTG USB

Interface

- Built-in 7 languages - English, French, German, Spanish, Chinese, Italian, Russian

Power

- Power supply: AC 110-240 V, 50/60 Hz
- Power consumption: ≤ 30 W
- Power standby: ≤ 1.5 W
- Power supply adapter: EU, UK or US

Installation

- Compatible with VESA
- For embedding
- Wall Mount

Housing

- Dimension: 293,6x193,6x48,5 mm (11.560x7.622x1.909 in)
- Construction: Aluminum alloy enclosure, color black
- Bezel thickness 3 mm

Environment

- Operating temperature: -10°C to 60°C (14°F to 140°F)
- Storage temperature: -10°C to 60°C (14°F to 140°F)
- Operation humidity: 10% to 80%
- Storage humidity: 10% to 90%
- Ingress Protection Rating: IP65 – for front panel

